

Built-In Cooktop

FPIC3677RF



Signature Features



Maximize Your Time PowerPlus™ Induction Technology boils water in less than 2 minutes so you can shave time off of cooking dinner every day.¹



Flexible Cooking
SpacePro™ Bridge Element allows you to cook two separate dishes at once, or combine elements for large pots or griddle use. The cooktop adapts to the size of the pan whether it's a small pot, a large frying pan or a griddle.



Gas Benefits, Without the Remodel

Our PowerPlus™ Induction Cooktop offers the the speed, control and consistency of gas, without requiring the converting of your kitchen from electric to gas.



Consistent Results
Even heat eliminates hot spots and
delivers consistent results for creating
delicious, evenly cooked foods like
steaks and omelettes.

36" Induction

Product Dimensions

 Width
 36"

 Depth
 20-1/8"

 Height
 2-7/8"

More Easy-To-Use Features

Cool Cooktop, Simple Cleanup Cool-to-the-touch cooktop generates heat directly to the pan, not the cooktop, so spills can't burn on.

Controlled Cooking

Adjusts from a powerful boil to a gentle simmer instantly — ideal for rice, soups and sauces.

Professional-Grade Controls

Heavy-duty knobs deliver precise temperature control, whether you're simmering, sautéing, searing or boiling.

Efficient Use of Power

The cooktop heats the pan directly so less heat is lost in the cooking process.

Cookware Compatible

Induction-friendly cookware includes most stainless steel or iron-based cookware. If a magnet sticks to the bottom of the cookware, it's compatible.

Available in:



Stainless (F)

Elements	Size	Watts
Right Front	10"	2,500/3,800
Right Rear	6"	1,450/2,000
Left Bridge	7"	1,800/2,600
Left Rear	7"	1,800/2,600
Centre	8"	2,300/3,200


¹10" induction right burner, 6 qt./10" diameter pot, 1 qt. tepid water.

FPIC3677RF **36" Induction**

Features	
Controls	Pro-Select* Controls
Surface Type	Black Ceramic Glass
Right Front Element (Watts)	10" - 2,500/3,800
Right Rear Element (Watts)	6" - 1,450/2,000
Left Bridge Element (Watts)	7" - 1,800/2,600
Left Rear Element (Watts)	7" - 1,800/2,600
Centre (Watts)	8" - 2,300/3,200
Hot Surface Indicators	Yes
Control Location	Centre Front
Knob Colour	Stainless
Knob Type	Cast Metal
Specifications	
Power Supply Connection Location	Right Rear
Voltage Rating	240V/208V/60Hz
Connected Load (kW Rating) @ 240/208 Volts ¹	12.0/10.4
Amps @ 240/208 Volts	50/50
Minimum Circuit Required (Amps)	40
Approved for Electric Single Wall Oven Combination Installation ²	Yes
Shipping Weight (Approx.)	53 Lbs.

Single phase 3- or 4-wire cable, 120/240 or 120/208 Volt, 60 Hertz AC only electrical supply with ground required on separate circuit fused on both sides of line.

²Cooktops are approved for installation above any of our Electric Single Wall Ovens.



NOTE: For planning purposes only. Always consult local and national electric codes. Refer to Product Installation Guide for detailed installation instructions on the web at frigidaire.ca.





Product Dimensions		Cutout Di
A - Width	36"	Width (Min
B-Depth	20-1/8"	Depth (Min
C-Height	2-7/8"	Height

Cutout Dimensions	
Width (Min.)/(Max.)	33-7/8"/34"
Depth (Min.)/(Max.)	19-1/8"/19-1/4"
Height	3-5/8"

Granite Countertop Installation Kit available.

Accessories information available on the web at **frigidaire.ca**